



S11750

14T8/LED/48-CCT/BP/FA8

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	14W
Color Temperature:	4000K/5000K/6500K
Length:	46.00"
Base:	Single Pin



TECHNICAL SPECIFICATIONS

Wattage:	14W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	180D
Fluorescent Equivalent:	30W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to +45C (+113F)
Filament:	LED	Bypass / Direct:	Ballast Bypass
Base:	Single Pin	Ballast Type:	Type B
ANSI Base:	Fa8	Single / Dual End:	Double Ended
Finish:	White	Shatter Proof Type:	PET Coated
Housing Color:	White	Safety Listing:	cRUus - Recognized Component; ETLus - Listed; cULus - Classified
Hours Rated:	50000H	Technology:	LED
Color Temperature:	4000K/5000K/6500K	Material:	Glass / Plastic
CRI:	83CRI		
Lumen Output:	1950L/2000L/1900L		

DIMENSIONS

MOL:	46.00"
MOD:	1.00"

LISTINGS

Safety Listing:	cRUus - Recognized Component; ETLus - Listed; cULus - Classified
Location Rating:	Damp
Energy Star:	No
UL File Listing:	CN/US - E335148; CN/US - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

PACKAGING

Each UPC:	045923117503
Each Quantity:	1
Each Dimensions:	48.00 x 1.00 x 1.00"

Case UPC:	10045923117500
Case Quantity:	10
Case Dimensions:	48.62 x 7.87 x 4.92"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2023
Satco Products, Inc.
All Rights Reserved
April 10, 2023