



S11766

14T8/LED/48-5CCT/BP/SE-DE

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	14W
Color Temperature:	3000K/3500K/4000K/5000K/6500K
Length:	47.17"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	14W	Dimmable:	Yes-Dimmable
Volts:	120V-277V	Beam Spread:	210D
Fluorescent Equivalent:	32W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to +45C (+113F)
Filament:	LED	Bypass / Direct:	Ballast Bypass
Base:	Medium Bi Pin	Ballast Type:	Type B
ANSI Base:	G13	Single / Dual End:	Single Ended, Double Ended
Finish:	White	Safety Listing:	cULus - Classified
Housing Color:	White	Technology:	LED
Hours Rated:	50000H	Material:	Glass / Plastic
Color Temperature:	3000K/3500K/4000K/5000K/6500K		
CRI:	80CRI		
Lumen Output:	1700L/1700L/1800L/1800L/1800L		

DIMENSIONS

MOL:	47.17"
MOD:	1.00"
Weight:	0.45

LISTINGS

Safety Listing:	cULus - Classified
Location Rating:	Damp
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-9MV7GT
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN/US - E335148; CN/US - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

PACKAGING

Each UPC:	045923117664	Case UPC:	10045923117661
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	47.80 x 0.94 x 0.94"	Case Dimensions:	48.66 x 5.87 x 5.75"

110 Heartland Blvd. Brentwood, NY 11717 PH 631-243-2022 FX 631-243-2027	Distribution Centers New York, Florida, Texas, Washington, California, Puerto Rico	National Toll-Free 800-43-SATCO (800-437-2826) www.satco.com	Copyright 2023 Satco Products, Inc. All Rights Reserved April 10, 2023
--	---	---	---