



# S11905

4W/LED/T5/840/BP  
 4W T5 LED; Miniature bi-pin base; 4000K; 50000 Average  
 rated hours; 400 Lumens; 120-277V; Type B; Ballast Bypass;  
 Double Ended Wiring



## Features

- No ballast or external driver required
- Available in 6", 9", 12", & 21"
- Direct wire 120-277V line voltage
- Double ended wiring
- NSF Approved
- PET Shatterproof coated
- 5 year Limited warranty

S11905

Replaces F8T5/CW lamps

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S11905	045923119057	120-277	4	50/60Hz	8W	0.90	T5
Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Miniature Bi-Pin	G5	4W/LED/T5/840/BP	Non-Dimmable	Frosted	11-29/32"	0-5/8"	400
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status
50000	4000	Cool White	80	240	-25C (-13F) to a maximum of +45C (+113F)	10	Lawful for sale in California
Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty			
Glass	Yes	Yes	cULus Classified - Damp Location Rated	<a href="#">5 Year Limited</a>			



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

