S11928

10T8/LED/48/840-850-865/DR

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	10W
Color Temperature:	4000K/5000K/6500K
Length:	48.00"
Base:	Medium Bi Pin

50,000 HOURS | **ENCLOSED FIXTURE** | **DLC** | **FC** | **RoHS COMPLIANT**

TECHNICAL SPECIFICATIONS

Wattage:	10W	Dimmable:		Yes-Dimmable
Volts:	120V-277V	Dimming Function:		Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Fluorescent Equivalent:	30W			
Shape:	T8			
Filament:	LED	Beam Spread:		220D
Base:	Medium Bi Pin	Power Factor:		0.9
ANSI Base:	G13	Operating Temp:		-20C (-4F) to a maximum of +45C (+113F)
Finish:	White			
Housing Color:	White	Ballasting Requirements:		Ballast required, check compatibility
Hours Rated:	50000H	Bypass / Direct:		Direct
Color Temperature:	4000K/5000K/6500K	Ballast Type:		Type A
CRI:	83CRI	Tube Guard Use:		Not Approved
Lumen Output:	1800L	Safety Listing:		cULus - Listed; cULus - Certified
		Technology:		LED
		Material:		Plastic

DIMENSIONS

MOL:	48.00"
MOD:	1.00"
Weight:	0.35

LISTINGS

Safety Listing:	cULus - Listed; cULus - Certified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PGH969QL
DLC Primary Use:	Replacement Lamps (plug and play) (UL Type A)
UL File Listing:	US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119286		Case UPC:	10045923119283
Each Quantity:	25		Case Quantity:	25
Each Dimensions:	50.00 x 6.50 x 6.70"		Case Dimensions:	50.00 x 6.50 x 6.70"