



S11943

23T5/LED/48-840/XD
 23W T5 LED; 4000K; 120-277V; Miniature Bi Pin base; Type C;
 External Driver required

Features

- All glass tube
- Approved for use with tube guards
- NSF Approved
- Working Voltage: 120-277VAC 43VDC 290mA
- 0-10V Dimming
- Satco External LED driver required for 1 or 2 lamps [S8012](#)
- Satco External LED driver required for 3 or 4 lamps [S8013](#)



S11943

Existing wiring to both sockets can remain in place.
 Will work on both shunted or non-shunted sockets.

| Item Number | UPC | Voltage | Watts | Operating Frequency | Fluorescent Equivalent | Power Factor | Lamp Shape |
|-------------|--------------|---------|-------|---------------------|------------------------|--------------|------------|
| S11943 | 045923119439 | 120-277 | 23 | 50/60HZ | 54W | 0.90 | T5 |

| Base | ANSI Base | Lamp Code | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches | Initial Lumens |
|------------------|-----------|--------------------|-----------------------|---------|---------------|---------------|----------------|
| Miniature Bi-Pin | G5 | 23T5/LED/48-840/XD | 0-10V Dimming Only | Frosted | 48" | 1.00" | 3400 |

| Average Rated Hours | Kelvin Temp | Color | CRI | Beam Spread Deg | Operating Temperature | Pack | Package Type |
|---------------------|-------------|------------|-----|-----------------|---|------|--------------|
| 50000 | 4000 | Cool White | 82 | 220 | -20C (-4F) to a maximum of +45C (+113F) | 25 | Sleeve |

| CEC Status | DLC ID: | Material | RoHS Compliant | UL or ETL Listed | UL Classification | Warranty |
|-------------------------------|--------------|----------|----------------|------------------|--|--------------------------------|
| Lawful for sale in California | PLCXVV6NDZC1 | Glass | Yes | Yes | cULus Classified - Damp Location Rated | 5 Year Limited |



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

