

Notes

www] 11-02-2020 01:57:0

| General | |
|-------------------------|----------------|
| Status | Active |
| Watts | 7 |
| Fluorescent Equivalent | 15 |
| Volts | 120V-277V |
| Ballast Type | Туре В |
| Shape | Т8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Nominal Length | 18.00 |
| Finish | Frosted |
| CCT (Kelvin) | 3000 |
| Temperature | Warm White |
| CRI | 83 |
| Lumens | 700 |
| Beam Spread | 160 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Linear |
| Technology | LED |
| Electrical | |
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60 Hz |
| | |

| Electrical | |
|-------------------------|--|
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60 Hz |
| Power Factor | 0.9 |
| THD | 25% |
| Operating Temperature | -25C (-13F) to a maximum of +40C (+104F) |

| Physical | |
|---------------|---------|
| MOL | 17.80 |
| MOD | 1.10 |
| Lens Finish | Frosted |
| Lens Material | Glass |
| Housing Color | White |

| Warranty | 5 Year Limited - T8 LED Bulbs - Ballast Bypass |
|-----------------|---|
| Compliance | |
| Safety Listing | cULus Classified; cRUus |
| Location Rating | Damp |
| CEC Status | Lawful for sale in California |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | ETL Sanitation listed (conforms to NSF) |

Additional Information

















