



S11966

30T8/LED/72-840/BP/R17D/HO

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	30WW
Color Temperature:	4000K
Length:	70"
Base:	Recessed Double Contact HO/VHO



TECHNICAL SPECIFICATIONS

Wattage:	30W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	160D
Fluorescent Equivalent:	87W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast Bypass
Base:	Recessed Double Contact HO/VHO	Bypass / Direct:	BallastBypass
ANSI Base:	R17d	Ballast Type:	Type B
Finish:	Frost	Single / Dual End:	Double Ended
Housing Color:	White	Tube Guard Use:	Yes
Hours Rated:	50000H	Shatter Proof Type:	Yes
Color Temperature:	4000K	Safety Listing:	cULus
CRI:	82CRI	Technology:	LED
Lumen Output:	4200L	Material:	Glass

DIMENSIONS

MOL:	70"
MOD:	1.1"
Weight:	1.01

LISTINGS

Safety Listing:	cULus
Location Rating:	Damp
Energy Star:	No
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119668	Case UPC:	10045923119665
Each Quantity:	1	Case Quantity:	10
Each Dimensions:	72.00 x 1.10 x 1.10"	Case Dimensions:	74.60 x 7.87 x 4.92"

110 Heartland Blvd.
 Brentwood, NY 11717
 PH 631-243-2022
 FX 631-243-2027

Distribution Centers
 New York, Florida,
 Texas, Washington,
 California, Puerto Rico

National Toll-Free
 800-43-SATCO
 (800-437-2826)
 www.satco.com

Copyright 2021
 Satco Products, Inc.
 All Rights Reserved
 October 24, 2021