



**S11970**

13T8U6/LED/22.5-830/DUAL

**GENERAL SPECIFICATIONS**

|                    |               |
|--------------------|---------------|
| Shape:             | T8            |
| Wattage:           | 13WW          |
| Color Temperature: | 3000K         |
| Length:            | 22.50"        |
| Base:              | Medium Bi Pin |



**TECHNICAL SPECIFICATIONS**

|                         |               |
|-------------------------|---------------|
| Wattage:                | 13W           |
| Volts:                  | 120V-277V     |
| Fluorescent Equivalent: | 32W           |
| Shape:                  | T8            |
| Filament:               | LED           |
| Base:                   | Medium Bi Pin |
| ANSI Base:              | G13           |
| Finish:                 | Frost         |
| Housing Color:          | White         |
| Hours Rated:            | 50000H        |
| Color Temperature:      | 3000K         |
| CRI:                    | 83CRI         |
| Lumen Output:           | 1900L         |

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimmable:                | Yes-Dimmable                                                                                                                                            |
| Dimming Function:        | Check Ballast MFG for Dimmer Compatibility; Only in Type A mode; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control |
| Beam Spread:             | 160D                                                                                                                                                    |
| Power Factor:            | 0.9                                                                                                                                                     |
| Operating Temp:          | -20C (-4F) to a maximum of +45C (+113F)                                                                                                                 |
| Ballasting Requirements: | Ballast required (Type A) or Ballast Bypass (Type B)                                                                                                    |
| Ballast Type:            | Type A/B                                                                                                                                                |
| Single / Dual End:       | Single Ended, Double Ended                                                                                                                              |
| Tube Guard Use:          | Yes                                                                                                                                                     |
| Shatter Proof Type:      | Yes                                                                                                                                                     |
| Safety Listing:          | cULus Classified; cULus Listed                                                                                                                          |
| Technology:              | LED                                                                                                                                                     |
| Material:                | Plastic                                                                                                                                                 |

**DIMENSIONS**

|              |        |
|--------------|--------|
| MOL:         | 22.50" |
| MOD:         | 1.1"   |
| Leg Spacing: | 6      |
| Weight:      | 0.91   |

**LISTINGS**

|                     |                                               |
|---------------------|-----------------------------------------------|
| Safety Listing:     | cULus Classified; cULus Listed                |
| Location Rating:    | Damp                                          |
| Energy Star:        | No                                            |
| DLC Approved:       | Yes                                           |
| DLC Classification: | Standard                                      |
| DLC ID:             | PLTOHYEACRK2                                  |
| DLC Primary Use:    | Replacement Lamps (plug and play) (UL Type A) |
| CEC Terse:          | Lawful for sale in California                 |
| RoHS Compliant:     | Yes                                           |
| FCC Compliant:      | Yes                                           |
| NSF Approved:       | Yes                                           |
| SDS Class:          | LED_Lamp                                      |

**PACKAGING**

|                       |                    |                  |                       |
|-----------------------|--------------------|------------------|-----------------------|
| Each UPC:             | 045923119705       | Case UPC:        | 10045923119702        |
| Each Quantity:        | 1                  | Case Quantity:   | 12                    |
| Each Dimensions:      | 22.50 x 6.00       | Case Dimensions: | 24.41 x 8.27 x 15.16" |
| Distribution Centers: | National Toll-Free | Case Copyright:  | 2021                  |
| B ; , Florida,        | 800-43-SATCO       |                  | Satco Products, Inc.  |
| PH 631-243-2022       | (800-437-2826)     |                  | All Rights Reserved   |
| FX 631-243-2027       | www.satco.com      |                  | October 24, 2021      |