



S11972

13T8U6/LED/22.5-840/DUAL

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	13WW
Color Temperature:	4000K
Length:	22.50"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	13W
Volts:	120V-277V
Fluorescent Equivalent:	32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Frost
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	4000K
CRI:	83CRI
Lumen Output:	2000L

Dimmable:	Yes-Dimmable
Dimming Function:	Check Ballast MFG for Dimmer Compatibility; Only in Type A mode; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Beam Spread:	160D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast required (Type A) or Ballast Bypass (Type B)
Ballast Type:	Type A/B
Single / Dual End:	Single Ended, Double Ended
Tube Guard Use:	Yes
Shatter Proof Type:	Yes
Safety Listing:	cULus Classified; cULus Listed
Technology:	LED
Material:	Plastic

DIMENSIONS

MOL:	22.50"
MOD:	1.1"
Leg Spacing:	6
Weight:	0.91

LISTINGS

Safety Listing:	cULus Classified; cULus Listed
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLX80LFIAOD6
DLC Primary Use:	Replacement Lamps (plug and play) (UL Type A)
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119729	Case UPC:	10045923119726
Each Quantity:	1	Case Quantity:	12
Each Dimensions:	22.50 x 6.00	Case Dimensions:	24.41 x 8.27 x 15.16"
Distribution Centers:	National Toll-Free	Case Copyright:	© Satco Products, Inc. 2021
Boston, Florida,	800-43-SATCO		All Rights Reserved
Texas, Washington,	(800-437-2826)		October 24, 2021
California, Puerto Rico	www.satco.com		