



S11978

10.5T8/LED/48-840/BP/SE-DE/PC

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	10.5W
Color Temperature:	4000K
Length:	47.78"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	10.5W
Volts:	120V-277V
Fluorescent Equivalent:	25W/28W/32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Frost
Hours Rated:	70000H
Color Temperature:	4000K
CRI:	83CRI
Lumen Output:	1650L

Beam Spread:	180D
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus - Classified; cRUus - Recognized Component
Technology:	LED
Material:	Plastic

DIMENSIONS

MOL:	47.78"
MOD:	1.00"

LISTINGS

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-PE2TIM
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

PACKAGING

Each UPC:	045923119781
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10"

Case UPC:	10045923119788
Case Quantity:	25
Case Dimensions:	50.00 x 6.50 x 6.69"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2023
Satco Products, Inc.
All Rights Reserved
April 10, 2023