



S11991

10.5T8/LED/48-850/BP/USA

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	10.5WW
Color Temperature:	5000K
Length:	47.78"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	10.5W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	210D
Fluorescent Equivalent:	30W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast Bypass
Base:	Medium Bi Pin	Bypass / Direct:	BallastBypass
ANSI Base:	G13	Ballast Type:	Type B
Finish:	Frost	Single / Dual End:	Single Ended, Double Ended
Housing Color:	White	Safety Listing:	cULus Classified; cRUus
Hours Rated:	50000H	Technology:	LED
Color Temperature:	5000K	Material:	Glass; Plastic
CRI:	82CRI		
Lumen Output:	1700L		

DIMENSIONS

MOL:	47.78"
MOD:	1.00"
Weight:	0.44

LISTINGS

Safety Listing:	cULus Classified; cRUus
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PL2TL5V4BLWF
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	E356871
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119910	Case UPC:	10045923119917
Each Quantity:	1	Case Quantity:	25
Each Dimensions:	48.00 x 1.00 x 1.00"	Case Dimensions:	48.80 x 6.10 x 6.30"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2021
Satco Products, Inc.
All Rights Reserved
October 24, 2021