



S11995

14T8/LED/48-850/BP/USA

GENERAL SPECIFICATIONS

| | |
|--------------------|---------------|
| Shape: | T8 |
| Wattage: | 14WW |
| Color Temperature: | 5000K |
| Length: | 47.78" |
| Base: | Medium Bi Pin |



TECHNICAL SPECIFICATIONS

| | | | |
|-------------------------|---------------|--------------------------|---|
| Wattage: | 14W | Dimmable: | Non-Dimmable |
| Volts: | 120V-277V | Beam Spread: | 210D |
| Fluorescent Equivalent: | 32W | Power Factor: | 0.9 |
| Shape: | T8 | Operating Temp: | -20C (-4F) to a maximum of +45C (+113F) |
| Filament: | LED | Ballasting Requirements: | Ballast Bypass |
| Base: | Medium Bi Pin | Bypass / Direct: | BallastBypass |
| ANSI Base: | G13 | Ballast Type: | Type B |
| Finish: | Frost | Single / Dual End: | Single Ended, Double Ended |
| Housing Color: | White | Safety Listing: | cULus Classified; cRUus |
| Hours Rated: | 50000H | Technology: | LED |
| Color Temperature: | 5000K | Material: | Glass; Plastic |
| CRI: | 82CRI | | |
| Lumen Output: | 1800L | | |

DIMENSIONS

| | |
|---------|--------|
| MOL: | 47.78" |
| MOD: | 1.00" |
| Weight: | 0.44 |

LISTINGS

| | |
|---------------------|--|
| Safety Listing: | cULus Classified; cRUus |
| Location Rating: | Damp |
| Energy Star: | No |
| DLC Approved: | Yes |
| DLC Classification: | Standard |
| DLC ID: | PL5XKL012IL2 |
| DLC Primary Use: | Internal Driver/Line Voltage (UL Type B) Lamps |
| UL File Listing: | E356871 |
| CEC Terse: | Lawful for sale in California |
| RoHS Compliant: | Yes |
| FCC Compliant: | Yes |
| NSF Approved: | Yes |
| SDS Class: | LED_Lamp |

PACKAGING

| | | | |
|------------------|----------------------|------------------|----------------------|
| Each UPC: | 045923119958 | Case UPC: | 10045923119955 |
| Each Quantity: | 1 | Case Quantity: | 25 |
| Each Dimensions: | 48.00 x 1.00 x 1.00" | Case Dimensions: | 48.80 x 6.10 x 6.30" |

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2021
Satco Products, Inc.
All Rights Reserved
October 24, 2021