

Project Name

Location

Prepared By



Notes

[www] 01-29-2021 11:42:02

**General**

Status	Active
Watts	80
Incandescent Equivalent	400
HID Equivalent	250
Volts	100V-277V
Shape	Comcob
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
CRI	80
Lumens	10400L - 11200L
Beam Spread	360
Dimmable	Dimmable with optional control modules
Hours Rated	50000
Technology	LED
Min Compartment Size	Length: 9.85 in. Width: 9.85 in. Depth: 10.95 in.

**Electrical**

Operating Frequency	50/60 Hz
Dimming Type	Smart
Power Factor	0.9
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to a maximum of 45C ( 113F)

**Physical**

MOL	9.8
MOD	5.2
Lens Finish	Clear
Lens Material	Plastic
Housing Color	White
Photocell	Yes
Weight (lb.)	3.30

**Additional Information**

Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	This is not to be used with a ballast
Warranty	5 Year Limited - Hi-Pro

**Compliance**

Safety Listing	cULus
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLLUNA05S0RW;PLQZVG5NED5L
California Status	Lawful for sale in California
RoHS Compliant	Yes

FCC Compliant

Yes

SDS Sheet

LED\_Lamp

