



S16408

30T8/LED/HO-SIGN/72-840/BP
 30W T8 LED; 4000K; 4100 Lumens; 120-277V; Type B; Single Ended; Ballast Bypass

Features

- Base rotates 90° for easy installation
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required



S16408

Item Number	UPC	Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S16408	045923164088	120-277	30	50/60Hz	T8	Recessed Double Contact HO/VHO	R17d

Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
30T8/LED/HO-SIGN/72-840/BP	Frosted	72"	1.00"	4100	50000	4000	Cool White

CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	RoHS Compliant	UL or ETL Listed
83	330	-40C (-40F) to a maximum of +45C (+113F)	10	Sleeve	Lawful for sale in California	Yes	Yes

UL Classification	Warranty
cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

