

S16409

30T8/LED/HO-SIGN/72-865/BP 30W T8 LED; 6500K; 4100 Lumens; 120-277V; Type B; Single Ended; Ballast Bypass

Features

- Base rotates 90° for easy installation
 Direct wire 120-277V line voltage*
 NSF Approved
 No ballast or external driver required



S16409

Item Number		UPC		Voltage		Wat	tts	Operating Frequency		Lamp Shape		Base		ANSI Base			
S16409 04			15923164095		120-277		30)	50/60	0Hz	٦	⊺8	8		d Double HO/VHO	R17d	
Lamp Code				Finish		MOL Inch			DD In ches	Initial Lumens			Average Rated Hours		Kelvin Temp	Color	
30T8/LED/HO-SIG 865/BP			I/72- Frosted		ed	72"		1	.00''	4100		50000			6500	Daylight	
CRI	CRI Beam Spread Op Deg Op			perating Temperature				Pack	Packag	је Туре СЕ		EC Status		RoHS Compliant		UL or ETL Listed	
83	330	30 -40C (-40F) to a maxi +45C (+113F)				of 10		Sleeve		Lawful for sale ir California			Yes		Yes		
	UL Classification													Warranty			
	cULus Classified - Damp Location Rated												5 Year Limited				



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051