



S16412

7T8/LED/HO-SIGN/18-840/BP
 7W T8 LED; 4000K; 950 Lumens; 120-277V; Double Side LED;
 Type B; Ballast Bypass; Single Ended Wiring

Features

- Base rotates 90° for easy installation
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required



S16412

Item Number	UPC	Voltage	Watts	Operating Frequency	Power Factor	Lamp Shape	Base
S16412	045923164125	120-277	7	50/60Hz	0.90	T8	Recessed Double Contact HO/VHO

ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	Nominal Length	MOD In Inches	Initial Lumens
R17d	7T8/LED/HO-SIGN/18-840/BP	Non-Dimmable	Frosted	15-7/8"	18"	1.00"	950

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
50000	4000	Cool White	83	330	-30C (-22F) to a maximum of +45C (+113F)	10	Sleeve

CEC Status	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Lawful for sale in California	Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

