



S16503

FC12T9/LED/CIR/830/BP
LED Circline; 16W; T9; 3000K; G10Q Base; 120-277V; Type B;
Ballast Bypass

Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- NSF Approved
- Replaces 32W fluorescent Circlines



S16503

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S16503	045923165030	120-277	16	50/60Hz	32W	0.90	T9

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium Bi-Pin	G10q	FC12T9/LED/CIR/830/BP	Non-Dimmable	White	1"	11.00"	1600

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	THD	Pack
50000	3000	Soft White	80	135	-25C (-13F) to a maximum of +45C (+113F)		12/1

Package Type	Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Box	Plastic	Yes	Yes	cETLus - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

