



## S18412

13T8/U3/LED/CCT/BP/SE-DE

### GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	13W
Color Temperature:	3000K/4000K/5000K
Length:	22.60"
Base:	Medium Bi Pin



### TECHNICAL SPECIFICATIONS

Wattage:	13W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	160D
Fluorescent Equivalent:	32W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast Bypass
Base:	Medium Bi Pin	Bypass / Direct:	Ballast Bypass
ANSI Base:	G13	Ballast Type:	Type B
Finish:	White	Single / Dual End:	Single Ended, Double Ended
Housing Color:	White	Safety Listing:	cRUus - Recognized Component; ETLus - Listed; cULus - Classified
Hours Rated:	50000H	Technology:	LED
Color Temperature:	3000K/4000K/5000K	Material:	Plastic
CRI:	80CRI		
Lumen Output:	1850L/1950L/1950L		

### DIMENSIONS

MOL:	22.60"
MOD:	1.00"
Leg Spacing:	3.00

### LISTINGS

Safety Listing:	cRUus - Recognized Component; ETLus - Listed; cULus - Classified
Location Rating:	Damp
Energy Star:	No
UL File Listing:	CN/US - E335148; CN/US - E356817; ETL - 4005203
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

### PACKAGING

Each UPC:	045923184123	Case UPC:	10045923184120
Each Quantity:	1	Case Quantity:	12
Each Dimensions:	22.50 x 1.00 x 1.00"	Case Dimensions:	23.63 x 10.55 x 8.27"

110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027

Distribution Centers  
New York, Florida,  
Texas, Washington,  
California, Puerto Rico

National Toll-Free  
800-43-SATCO  
(800-437-2826)  
www.satco.com

Copyright 2023  
Satco Products, Inc.  
All Rights Reserved  
April 10, 2023