

## S21711

5A15/LED/27K/CL/E26/120V/CD 5 watt; A15 LED; Clear; 2700K; Medium base; 120 volts; Carded

## Features

- LED with a traditional incandescent look and feel
  Omni-directional light source
  Smooth dimming
  Replaces up to 40 watt lamps
  Long life 15,000 hours
  Damp Location
  UL listed for totally enclosed fixtures



S21711

| Item Number UPC             |                     |     | Voltage | Watts                     | Incandescent                            | Incandescent Equivalent             |        |                             | Bas            | se            | ANSI Base      |                           |  |
|-----------------------------|---------------------|-----|---------|---------------------------|---|-------------------------------------|--------|-----------------------------|----------------|---------------|----------------|---------------------------|--|
| S21711                      | S21711 045923217111 |     |         | 120                       | 5                                       | 40\                                 | 40W    |                             | A15            |               | um             | E26                       |  |
| Lamp Code                   |                     |     |         | Dimmable/Non-<br>Dimmable |   | Suggested<br>Dimmers                | Finish | MOL Ir<br>Inches            |                | Initi<br>Lume |                | Average<br>Rated<br>Hours |  |
| 5A15/LED/27K/CL/E26/120V/CD |                     |     |         | Dimmable                  |   | Compatible<br>dimmers for<br>S21711 | Clear  | 3-5/8''                     | 1-7/8"         | 45            | 0              | 15000                     |  |
| Kelvin Temp Color CRI Bea   |                     |     |         | n Spread<br>Deg           | Ope                                     | rating Temperature                  |        | Pack                        | Package        | age Type      |                | ENERGY STAR               |  |
| 2700                        | Warm White          | 80  |         | 360                       | -20C (-4F) to a maximur<br>+45C (+113F) |                                     | Im of  | 12/2                        | CD/2           |               | ENERGY STAR    |                           |  |
| CEC Status RoHS Compliant   |                     |     | pliant  | Fixture Type              |   | UL or ETL<br>Listed                 | UL     |                             | Classification |               | Warranty       |                           |  |
| Non-Compl                   | iant                | Yes |         | Enclosed Rated            |   | Yes                                 | cULus  | cULus - Damp Location Rated |                |               | 3 Year Limited |                           |  |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051