

S21722

4.5W CFC/LED/5K/CL/120V/2CD 4.5W CA10 LED; Clear; Candelabra base; 5000K; 120V; Carded

Features

- · LED with a traditional incandescent look and feel

- LED with a traditional incandescent id
 Omni-directional light source
 Smooth dimming
 Replaces up to 40 watt lamps
 Long life 15,000 hours
 Damp Location
 UL listed for totally enclosed fixtures



S21722

Item Number	r UPC	UPC		Watts	Incandescent Equivalent			Powe Facto		Lamp Shape	Base
S21722	0459232	45923217227		4.5		40W		>0.9	0	CA10	Candelabra
ANSI Base	I amp Code			Dimmab Dimm		Finish	MOL Inch		OD In nches	Initial Lumens	Average Rated Hours
E12 4.	2 4.5W CFC/LED/5K/CL/120V/2C			Dimm	able	Clear	3 7/3	8" 1	-3/8''	350	15000
Kelvin Temp	Temp Color CRI Beam Spre Deg			^{ad} O	d Operating Temperature			Pack	Packa	age Type	ENERGY STAR
5000	Natural Light	80	360	-200	-20C (-4F) to +40C		n of	12	CD/2		ENERGY STAR
CEC Stat	us RoHS	RoHS Compliant		Fixture Type		UL or ETL Listed		UL Classification		ion	Warranty
Non-Comp	liant	Yes		Enclosed Rated Lamp		Yes	cULu	cULus - Damp Location Rated			3 Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051