

## S21730

4.5W ETC/LED/5K/CL/120V/2CD 4.5W B11 LED; Clear; Medium base; 5000K; 120V; Carded

## Features

- · LED with a traditional incandescent look and feel
- Omni-directional light source

- Offini-directional light source
  Smooth dimming
  Replaces up to 40 watt lamps
  Long life 15,000 hours
  Damp Location
  UL listed for totally enclosed fixtures



S21730

Item Numbe	r UP	С	Voltage	Watts	Incande	scent Equ	ıivalent	Pow Fac		Lamp Sh	ape	Base
S21730	0459232	17302	120	4.5		40W		0.7	70	B10/B1	1	Medium
ANSI Base	Lamp	Code		Dimmable/N Dimmabl		Finish	MOL In		DD In ches	Initial Lumens	; F	Average Rated Hours
E26 4.	5W ETC/LED/	5K/CL/12	0V/2CD	Dimmabl	le	Clear	3 7/8"	1.	-3/8''	350		15000
Kelvin Temp	Color	CRI <sup>I</sup>	Beam Spread Deg	Ope	rating Te	emperatui	re	Pack	Packa	age Type	ENE	RGY STAR
5000	Natural Light	80	360	-20C (-	4F) to a +40C (	maximun 104F)	n of	12/2	C	CD/2 ENI		RGY STAR
CEC Status RoHS Compliant			nt Fixtu	re Type UL or ETL Listed			UL Classification		١	Varranty		
Non-Comp	liant	Yes Enclosed R		Rated Lam	np Yes cUL		cULus	JLus - Damp Location Rated			3 Y	ear Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051