



S21925

40T8/LED/96-865/BP/FA8

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	40W
Color Temperature:	6500K
Length:	94.00"
Base:	Single Pin



TECHNICAL SPECIFICATIONS

Wattage:	40W
Volts:	120V-277V
Fluorescent Equivalent:	59W
Shape:	T8
Filament:	LED
Base:	Single Pin
ANSI Base:	FA8
Finish:	White
Hours Rated:	50000H
Color Temperature:	6500K
CRI:	82CRI
Lumen Output:	5500L

Dimmable:	Non-Dimmable
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Double Ended
Shatter Proof Type:	PET Coated
Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Technology:	LED
Material:	Glass

DIMENSIONS

MOL:	94.00"
MOD:	1.00"
Weight:	0.88

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLXALFHWUTHG
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	US/CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923219252	Case UPC:	10045923219259
Each Quantity:	1	Case Quantity:	10
Each Dimensions:	94.00 x 1.00 x 1.00	Case Dimensions:	95.87 x 7.56 x 3.86
1 on Centers		Copyright 2022	
Brentwood, NY 11717	New York, Florida,	800-43-SATCO	Satco Products, Inc.
PH 631-243-2022	Texas, Washington,	(800-437-2826)	All Rights Reserved
FX 631-243-2027	California, Puerto Rico	www.satco.com	May 22, 2022