

## S29672

36W/LED/HID/2700K/100-277V/E26 36 watt - LED HID Replacement; 2700K; Medium base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
  UL approved for totally enclosed fixtures
- Wet location rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
  Working Voltage AC90-305V

| Minimum Compartment Size |           |           |  |  |  |  |  |
|--------------------------|-----------|-----------|--|--|--|--|--|
| Length                   | Width     | Depth     |  |  |  |  |  |
| 17.3 inch                | 9.25 inch | 9.25 inch |  |  |  |  |  |

**Optional Accessories** 

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406

This item has been discontinued. Possible replacement:

• S39672



S29672

| Item   | Product | UPC | Input<br>Voltage | Watts | Operating | Incandescent | Fluorescent |
|--------|---------|-----|------------------|-------|-----------|--------------|-------------|
| Number | Line    | UFG |                  |       | Frequency | Equivalent   | Equivalent  |

| S29672          | Hi-Pro                           | 045923       | 3296727             | 100 - 277           | 36       | 50/60H              | Ηz             | 200W                 |                            |                  | 55W                    |  |
|-----------------|----------------------------------|--------------|---------------------|---------------------|----------|---------------------|----------------|----------------------|----------------------------|------------------|------------------------|--|
| HID Equivalent  | Base                             | ANSI<br>Base |                     | Lamp Cod            | e        |                     | mmabl<br>Dimma |                      | Finish                     | MOL In<br>Inches | MOD In<br>Inches       |  |
| 150W            | Medium                           | E26          | 36W/LED/H           | HD/2700K/1          | 00-277V/ | 'E26 No             | on-Dim         | mable                | White                      | 9-1/4''          | 3.69"                  |  |
| Initial Lumens  | Average Ra<br>Hours              |              | Kelvin Temp         | o Color             | CRI      | Beam Sp<br>Deg      |                | Оре                  | erating Tem                | perature         | Pack                   |  |
| 4390            | 50000                            |              | 2700                | Warm Whi            | te 80+   | 300                 |                | -20C                 | (-4F) to a ma<br>+65C (+14 |                  | f 12                   |  |
| Package<br>Type | CEC Status                       |              | RoHS<br>compliant I | UL or<br>ETL Listed | UL Clas  | sification          | Wa             | rranty               | Status                     |                  | uggested<br>Substitute |  |
| Box             | Lawful for sale<br>in California | )            | Yes                 | Yes                 |          | s - Wet<br>on Rated |                | <u>rear</u><br>nited | Discontinu                 | ed               | <u>S39672</u>          |  |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051