

S29677

120W/LED/HID/4000K/100-277V/EX39 120 watt - LED HID Replacement; 4000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
- Damp location IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- Built-in surge protection 5KV
- 5 year limited warranty
- Classified under UL 1598C
- · Safety chain included

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in surge protection

Minimum Compartment Size								
Length	Width	Depth						
17.3 inch	9.25 inch	9.25 inch						

Optional accessory: In-line surge protector 80-929

This item has been discontinued. Possible replacement:

• <u>S39677</u>



S29677

S29	9677	Hi-Pro	045923296	6772	100 - 277		120 5	0/60Hz	60Hz 750		V 200W		
	HID iivalent	Base	ANSI Base		Lamp Code				Dimmable/Non-Fir		MOL In Inches	MOD In Inches	
60	00W	Mogul Extended	EX39	120V	120W/LED/HID/4000K/100- 277V/EX39			Non-E	Non-Dimmable W		10-3/8"	5-7/8"	
Initial Average Rated Kelvi Lumens Hours Tem		C	olor	CRI	Beam Sprea Deg	d Burniı	Burning Position		Operating Temperature				
15600		50000	400	Cool White		80+	300		Up or Down Operation Only		-20C (-4F) to a maximum of +65C (+149F)		
Pack	Package Type	e CEC Status	DLC	ID:	RoH Comp		UL Classification	Warranty	Thermal Manageme	ent (Status	Suggested Substitute	
4	Box	Lawful for sale in California	PL1YPC7YDO1H; PLGH793AQSRY DLC Search		Ye	S	cULus - Wet Location Rated	5 Year Limited	More Detai	Disc	continued	<u>\$39677</u>	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051