

## S29904

17T8/LED/48-830/BP 120-277V 17 watt T8 LED; 3000K; Medium Bi Pin base; 50000 Average rated hours; 2100 Lumens

## Features

- All glass tube
- Approved for use with tube guards
  Direct wire 120-277V line voltage\*
  NSF Approved

- No ballast or external driver required
  Built-in shock resistant circuit (not hot until both ends are installed)

S29904

\*Existing wiring to both sockets can remain in place \*Will work on both shunted or non-shunted sockets

Item Num	ber	UPC		Voltag	ge Watts		Operating Frequency		Fluorescent Equivalent			Lamp Shape	Base	
S29904	0459	045923299049		120-27	77 17		50/60Hz			32W		T8	Medium Bi- Pin	
ANSI Base	Lamp Code			Dimmable/Non- Dimmable			Finish	MOL In Inches		MOD In Inches		iitial mens	Average Rated Hours	
G13		17T8/LED/48-830/BP 120-277V			n-Dimmab	le	White	48"		1.00"	2	100	50000	
Kelvin Temp	Color	CRI		ı Spread Deg Operatir			g Temperature		ack	CEC Status		DLC ID:		
3000	Soft White	82	2	10	•	'	a maximum of (+113F)		25	Lawful for sale in California		PL6P5PDAP8FX DLC Search		
RoHS Compliant			UL or ETL Listed			UL Classification						Warranty		
Yes			Yes			cULus Classified - Damp Location Rated						5	5 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051