



S29916

14T8/LED/48-850/BP 120-277V
 14W T8 LED; Medium bi-pin base; 5000K; 50000 Average
 rated hours; 1800 Lumens; Type B; Ballast Bypass; Double
 Ended Wiring

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29916

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29916	045923299162	120-277	14	50/60Hz	25W-32W	T8	Medium Bi-Pin

ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	14T8/LED/48-850/BP 120-277V	Non-Dimmable	White	48"	1.00"	1800	50000

Kelvin Temp	Color	CRI	Beam Spread Deg	Pack	Package Type	CEC Status	DLC ID:
5000	Natural Light	82	210	25	Box	Lawful for sale in California	PLZBOEH3B9H7 DLC Search

RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

