



S29925

40T8/LED/96-850/BP/R17D

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	40W
Color Temperature:	5000K
Length:	94.00"
Base:	Recessed Double Contact HO/VHO



TECHNICAL SPECIFICATIONS

Wattage:	40W
Volts:	120V-277V
Fluorescent Equivalent:	110W
Shape:	T8
Filament:	LED
Base:	Recessed Double Contact HO/VHO
ANSI Base:	R17d
Finish:	White
Hours Rated:	50000H
Color Temperature:	5000K
CRI:	82CRI
Lumen Output:	5500L

Dimmable:	Non-Dimmable
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Double Ended
Shatter Proof Type:	PET Coated
Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Technology:	LED
Material:	Glass

DIMENSIONS

MOL:	94.00"
MOD:	1.00"
Weight:	0.88

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
UL File Listing:	US/CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923299254
Each Quantity:	1
Each Dimensions:	94.00 x 1.00 x 1.00"

Case UPC:	10045923299251
Case Quantity:	10
Case Dimensions:	95.87 x 7.56 x 3.86"

110 Heartland Blvd.
 Brentwood, NY 11717
 PH 631-243-2022
 FX 631-243-2027

Distribution Centers
 New York, Florida,
 Texas, Washington,
 California, Puerto Rico

National Toll-Free
 800-43-SATCO
 (800-437-2826)
 www.satco.com

Copyright 2022
 Satco Products, Inc.
 All Rights Reserved
 May 22, 2022