



S29927

12T8/LED/36-835/BP 120-277V
 12W T8 LED; Medium bi-pin base; 3500K; 50000 Average
 rated hours; 1400 Lumens; Type B; Ballast Bypass; Double
 Ended Wiring

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29927

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

| Item Number | UPC | Voltage | Watts | Operating Frequency | Fluorescent Equivalent | Lamp Shape | Base |
|--|-----------------------------|-----------------------|------------------|---|--------------------------------|----------------|-------------------------------|
| S29927 | 045923299278 | 120-277 | 12 | 50/60Hz | 25W | T8 | Medium Bi-Pin |
| ANSI Base | Lamp Code | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches | Initial Lumens | Average Rated Hours |
| G13 | 12T8/LED/36-835/BP 120-277V | Non-Dimmable | White | 36" | 1.00" | 1400 | 50000 |
| Kelvin Temp | Color | CRI | Beam Spread Deg | Operating Temperature | Pack | Package Type | CEC Status |
| 3500 | Neutral White | 82 | 210 | -20C (-4F) to a maximum of +45C (+113F) | 25 | Box | Lawful for sale in California |
| DLC ID: | | RoHS Compliant | UL or ETL Listed | UL Classification | Warranty | | |
| PLZCLRCISTTC DLC Search | | Yes | Yes | cULus Classified - Damp Location Rated | 5 Year Limited | | |



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

