

S29990

10T8/LED/36-830/DR

10W T8 LED; 3000K; Medium Bi Pin base; 50000 Average rated hours; 1400 Lumens; Type A; Ballast dependent

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
 Solid State LED lighting
 Compatible with emergency ballasts*
 25watt Fluorescent equivalency

- 5 year Limited warranty

*May not be compatible with all rapid start, dimmable, and emergency ballasts.

Ballast required

View: **Ballast Compatibility Chart**

Item I	Number	UPC		Watts		orescent juivalent	Lamp Shape	Base		ANSI L Base		₋amp Code	
S2	9990	045923299902		10	25W		T8	Medium Bi- Pin		G13	10T8/LED/		36-830/DR
Dimn	nable/Non-[Dimmable	Finish	Finish MOL Inch		MOD In Inches	A Initial Lumens		verage Houi		^d Kelvin Tem		Color
Non-Dimmable			White	36"		1.00"	1400		5000	000 3)	Soft White
CRI	Beam Spread De	g Opera	perature	Pack	Package Type	CEC Status			DLC ID:			RoHS ompliant	
82	220	-20C (-4F) to a maxir of +45C (+113F)			10	Box	Lawful for sale in California		PLNQ\ DLC S	WK64AP91 Search			Yes
UL or ETL Listed						UL Classification			Warranty				
	Ye	S			cULus - Damp Location Rated					5 Year Limited			

S29990



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051