

S29993

10T8/LED/36-850/DR 10W T8 LED; 5000K; Medium Bi Pin base; 50000 Average rated hours; 1450 Lumens; Type A; Ballast dependent

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
 Compatible with emergency ballasts*
- 25watt Fluorescent equivalency
- 5 year Limited warranty

*May not be compatible with all rapid start, dimmable, and emergency ballasts.

S29993

Ballast required

View:

Ballast Compatibility Chart

Item Number		UPC		Watts		orescent quivalent	Lamp Shape		ise	ANSI Base		Lamp Code		
S29993 045923			923299933		10	25W		Т8	Medium Bi- Pin		G1:	3	10T8/I	LED/36-850/DR
Dimmable/Non-Dimmabl			able F	inish	MOL Inch		MOD In Inches	Initial Lumens Av		erage Ra Hours			elvin emp	Color
	Non-Dimmable			/hite	36'	'	1.00"	1450		50000		5	000	Natural Light
CRI	I Beam I Spread Deg Operating Ter				nperature Pack		Package Type	CEC Sta	atus	DLC ID:		RoHS Compliant		
82	220	o -20C (-4F) to a of +45C (+				10 Box		Lawful for sale in California		PLL7TMUQ9WVL DLC Search			Yes	
UL or ETL Listed						UL Classification				Warranty				
Yes					cULus - Damp Location Rated						5 Year Limited			



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051