

S39393

45W/LED/HID/5000K/100-277V/EX39 45 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- High-bay / Low-bay / Post-top
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 4KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size							
Length	Width	Depth					
8 inch	8 inch	11 inch					

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39393

Item	Product		Input	Watts	Operating	Incandescent	Fluorescent
Number	Line	UFC	Voltage		Frequency	Equivalent	Equivalent

S39393	Hi-Pro (045923303937		100 - 277	45		50/60Hz		300W			65W	
HID Equivalent	Base	ANSI Base	Lamp Code				Di	Dimmable/Non- Dimmable			MOL In Inches	MOD In Inches	
175W	Mogul Extended	EX39	45W/LED/HID/5000K/100- 277V/EX39				N	Non-Dimmable			8-13/16"	3-11/32"	
Initial Lumens	Average Ra Hours	ted	Kelvin Temp	Color	С	RI ^{Be}	am Spr Deg	ead	Ор	erating Terr	nperature	Pack	
6435	50000		5000	Natural Li	ght 8	30	300		-20C	-20C (-4F) to a max +65C (+149		12	
Package Type	CEC Status	[DLC ID:	Mat	erial	Rol Com	HS pliant	UL ETL I	. or Listed	UL Classifi	cation	Warranty	
Box	Lawful for sale in California	L271R DLC S	HFVSJW <u>earch</u>	Alum	inum	Ye	es	Y	es	cULus - D Location F		<u>5 Year</u> Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051