

## S39395

80W/LED/HID/5000K/100-277V/EX39 80 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
  Damp location IP64 rated
- For outdoor & indoor use
- High-bay / Low-bay / Post-top
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 6KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size						
Length	Width	Depth				
9.25 inch	9.25 inch	17.32 inch				

**Optional Accessories** 

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39395

Item	Product		Input	Watts	Operating	Incandescent	Fluorescent
Number	Line	UFC	Voltage		Frequency	Equivalent	Equivalent

S39395	Hi-Pro	045923303	8951 100 - 277 80		80	50/6	/60Hz 400W		W	100W		
HID Equivalen	t Base	ANSI Base		Lamp Code			Dimmable/Non- Dimmable		Finish	MOL In Inches	MOD In Inches	
320W	Mogul Extended	EX39	80W/LED/HID/5000K/100- 277V/EX39			-	Non-Dimmable		White	8"	4-23/32"	
Initial Lumens		elvin emp	Color CRI			eam Spread Operat		ating Temperature		Pack		
11440	5000	00 5	000	Natural I	_ight	80	З			<sup>F</sup> ) to a maximum of 65C (+149F)		12
Package Type	CEC Status	DLC ID:	Ма	aterial	Rol Com	HS pliant	UL or ETL Listed	UL CI	assification	Warra	ntv	hermal nagement
Box	Lawful for sale in California	L8R5JIJ5444 DLC Search	l Alu	minum	Ye	es	Yes		ıs - Damp tion Rated	<u>5 Yea</u> Limite		<u>e Details</u> <u>About</u>



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051