

S39396

100W/LED/HID/5000K/100-277V/EX39 100 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- High-bay / Low-bay / Post-top
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 6KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size									
Length	Width	Depth							
9.25 inch	9.25 inch	17.32 inch							

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39396

S39396	Hi-Pro	045923303968		100 - 27	7 1	100	50/60Hz		500W		•	150W	
HID Equivalen	Base	ANSI Base	Lamp Code			Dimmable/Non- Dimmable		Finish	MOL In Inches	MOD In Inches			
400W	Mogul Extende	d EX39	10	00W/LED/H 277V	ID/500 /EX39		-	Non-Dimmable		White	9"	4-23/32"	
Initial Lume	Average ns Hou		Kelvin Temp	Cold	or	CRI	Beam S De		Operating Temperature Pac		Pack		
14300	500	00	5000	Natural	Light	80	30	0) to a m 5C (+14	aximum o	f 12	
Package Type	CEC Status	DLC II	D:	Material		oHS npliant	UL or ETL Listed	UL C	Classification	Warra	intv	hermal nagement	
Вох	Lawful for sale in California	LPJL30QF		Aluminum	Υ	′es	Yes		us - Damp ation Rated	<u>5 Ye</u> Limit	_	re Details About	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051