

S39670

18W/LED/HID/2700K/100-277V/E26

18 watt LED HID Replacement; 2700K; Medium base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 2.5KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size						
Length	Width	Depth				
8.5 inch	6 inch	6 inch				

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39670

Item	Product		Input	Watts	Operating	Incandescent	Fluorescent
Number	Line	Voltage	vvalis	Frequency	Equivalent	Equivalent	

S39670	Hi-Pro	0459	923306709	100 - 2	77 18	8	50/60Hz	12	20W		32W
HID Equivale	nt Base	ANS Bas		Lamp	Code			ble/Non- mable	Finish	MOL In Inches	MOD In Inches
70W	Mediu	m E26	6 18W/LE	D/HID/270	0K/100-2	77V/E26	Non-Di	immable	White	5.5	2-3/8"
Initial Lumen		e Rated ours	Kelvin Temp	Color	CRI	Beam S De	· DUI	ning Position	Oper	ating Ter	nperature
2340	50	000	2700	Warm White	80	30	D	Universal		4F) to a n +65C (+1	naximum of 49F)
Pack Package Type CEC Status Material RoHS Compliant UL or ETL Listed UL Classification Warranty											
48	Box	Non-Cor	npliant A	luminum	Y	es	Yes		Damp Loca Rated	ation 5	Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051