

## S39673

45W/LED/HID/4000K/100-277V/EX39 45 watt - LED HID Replacement; 4000K; Mogul extended base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
  Damp location IP64 rated
- For outdoor & indoor use
- High-bay / Low-bay / Post-top
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 4KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size								
Length	Width	Depth						
8 inch	8 inch	11 inch						

## Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39673

S39673	Hi-Pro	045923306730		100 - 277	45	50	50/60Hz		300W		65W	
HID Equivalent	Base	ANSI Base	I amn (:oc		le			mmable/No Dimmable	on- Finish	MOL In Inches	MOD In Inches	
175W	Mogul Extended	EX39	45W/	LED/HID/40/ 277V/EX3		00-	No	on-Dimmab	le White	8-13/16"	3-11/32"	
Initial Lumens	Average Rated Kelvin Temp Color CRI Beam Spread  Mens Hours Clor CRI Deg							1	Pack			
6300	50000	)	4000	Cool White	80	;	300	-20	-20C (-4F) to a maximu +65C (+149F)			12
Package Type	CEC Status	ī	DLC ID:	Material		RoHS Complia		UL or ETL Listed	UL Classi	fication	ation Warranty	
Вох	Lawful for sale in California		70MYG6 Search	Aluminu	m	Yes		Yes	cULus - Damp Location Rated		5 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051