



**S39720**

25T5/LED/46-865/BP/HO/SE-DE

**GENERAL SPECIFICATIONS**

Shape:	T5
Wattage:	25W
Color Temperature:	6500K
Length:	46.00"
Base:	Miniature Bi Pin



**TECHNICAL SPECIFICATIONS**

Wattage:	25W
Volts:	120V-277V
Fluorescent Equivalent:	54W
Shape:	T5
Filament:	LED
Base:	Miniature Bi Pin
ANSI Base:	G5
Finish:	Frost
Housing Color:	Silver
Hours Rated:	50000H
Color Temperature:	6500K
CRI:	83CRI
Lumen Output:	3400L

Dimmable:	Yes-Dimmable
Beam Spread:	180D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Tube Guard Use:	Not Approved
Safety Listing:	cULus - Classified; cULus - Certified
Technology:	LED
Material:	Aluminum

**DIMENSIONS**

MOL:	46.00"
MOD:	0.83"
Weight:	0.20

**LISTINGS**

Safety Listing:	cULus - Classified; cULus - Certified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PILKXR6N
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	US/CN - E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

**PACKAGING**

Each UPC:	045923397202
Each Quantity:	1
Each Dimensions:	46.00 x 1.00 x 1.00"

Case UPC:	10045923397209
Case Quantity:	25
Case Dimensions:	46.00 x 5.20 x 5.20"

110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027

Distribution Centers  
New York, Florida,  
Texas, Washington,  
California, Puerto Rico

National Toll-Free  
800-43-SATCO  
(800-437-2826)  
www.satco.com

Copyright 2022  
Satco Products, Inc.  
All Rights Reserved  
May 22, 2022