SATCO NUVO

Project Name

Location

Prepared By



SATCO S39751

40W/LED/HID/MB-G3/50K/100-277V

Notes

General	
Status	Active
Watts	40
Incandescent Equivalent	300
Fluorescent Equivalent	65
HID Equivalent	175
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80
Lumens	5600
Beam Spread	120;150;260
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	LED HID
Technology	LED
Min Compartment Size	Width 8.00 In. Depth 8.00 In. Height 11.00 In.
Electrical	
Operating Frequency	50/60 Hz
Power Factor	>0.9
Surge Protection	Built-in surge protection - 4KV
THD	<20%
Operating Temperature	-20C (-4F) to a maximum of +65C (+149F)
Physical	
MOL	7.24
MOD	3.35
Housing Color	White
Photocell	Optional Add-On
Weight (lb.)	1.85
Additional Information	
Additional Info	PIR Sensor available as an accessory
Enclosure Rating	Enclosed Rated Lamp
Rated For Enclosed Fixture	Yes
IP Rating	IP64
	Closed 260 deg: Partial 150 deg:
Specification Note	Closed 260 deg; Partial 150 deg; Open 120 deg

Compliance
Safety Listing

Location Rating



Damp



cULus Classified





Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
SDS Sheet	LED Lamp









