## SATCO NUVO

Project Name

Location

Prepared By



## Notes

60W/LED/HID/MB-G3/27K/100-277V

General	
	Antivo
Status	Active
Watts	60
Incandescent Equivalent	500
Fluorescent Equivalent	85
HID Equivalent	250
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	2700
Temperature	Warm White
CRI	
Lumens	7680
Beam Spread	120;150;260
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	LED HID
Technology	LED
Min Compartment Size	Width 9.30 In. Depth 9.30 In. Height 9.80 In.
Electrical	
Operating Frequency	50/60 Hz
Power Factor	>0.9
Surge Protection	Built-in surge protection - 4KV
THD	<20%
Operating Temperature	-20C (-4F) to a maximum of +65C (+149F)
Physical	
MOL	7.76
MOD	4.13
Housing Color	White
Photocell	Optional Add-On
Weight (lb.)	2.05
, ,	2.00
Additional Information	
Additional Info	PIR Sensor available as an accessory
Enclosure Rating	Enclosed Rated Lamp
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	Closed 260 deg; Partial 150 deg; Open 120 deg
Warranty	5 Year Limited - Hi-Pro
Compliance	
Safety Listing	cULus Classified

Location Rating



Damp







Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
SDS Sheet	LED Lamp









