SATCO' NUVO

Project Name

Location

Prepared By



SATCO S39900

9T8/LED/24-830/BP/SE-DE

Notes

| Status | Active |
|-------------------------|---------------------------------------|
| Watts | 9 |
| Volts | 120-277V |
| Ballast Type | Туре В |
| Shape | Т8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Finish | Gloss White |
| CCT (Kelvin) | 3000 |
| Temperature | Warm White |
| CRI | 82 |
| Lumens | 1100 |
| Beam Spread | 210 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Т8 |
| Technology | LED |
| Electrical | |
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60 Hz |
| Power Factor | 0.9 |
| THD | 0.2 |
| Operating Temperature | -20C (-4F) to a maximum of 45C (113F) |
| Physical | |
| MOL | 24.00 |
| MOD | 1.1 |
| Material | Glass |
| Lens Material | Glass |
| | |

Additional Information

Weight (lb.)

| Warranty | 5 Year Limited - T8 LED Bulbs - Ballast Bypass |
|-------------------|---|
| Compliance | |
| Safety Listing | cULus Classified |
| Location Rating | Damp |
| California Status | Lawful for sale in California |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |

0.24

For More Information Visit: <u>https://www.satco.com/</u>

