

## S8533

9WPLH/LED/840/BP/2P 9W LED PL 2-Pin; 4000K;1000 Lumens; G24d base; 50000 Average rated hours; 120 Deg. beam spread; Horizontal; Type B; Ballast Bypass



## Features

82

120

- In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13, 18, and 26 watt CFLs
- Ballast Bypass; Direct wire voltage range 100-277V
- Instant on to full brightness / no flickering
- Horizontal operation
- Up to 70% energy saving

S8533

Yes

5 Year Limited

Installation Note: 2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.

Horizontal

Operation

50/10

Item Number	UPC	Voltage Watts		Operating Frequency		Fluorescent Equivalent		Lamp Shape	Base
S8533	045923085338	120-277	77 9 50/60Hz		18, 26, G24d Socket; 13, 18, 26 G24q Socket		PL	G24d	
Lamp Code		Dimmable/Non- Dimmable		Finish	MOL In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
9WPLH/LED/840/BP/2P		Non-Dimm	Non-Dimmable		6-5/8"	1000	50000	4000	Cool White
CRI Beam Spread CRI Deg Burning Position Pack Package Type CEC Status RoHS Compliant							ant Wa	rranty	

Box

Lawful for sale in

California



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051