

S8535

9WPLV/LED/827/BP/2P

9W LED PL 2-Pin; 2700K; 900 Lumens; G24d base; 50000 Average rated hours; 120 Deg. beam spread; Vertical; Type B; Ballast Bypass

Features

- In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13, 18, and 26 watt CFLs Ballast Bypass; Direct wire voltage range 100-277V
- Instant on to full brightness / no flickering
- Vertical operation
- Up to 70% energy saving



Installation Note: 2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.

| Item Number | | UPC | | Volta | ge Wa | Vatts Operatir Frequen | | | • | Fluorescent Equivalent | | | amp hape | Base | |
|---------------------|--------------------------------|-----|------------|--------------|---------------------------|---------------------------|-------|--------------------|--|------------------------|------------------------|------------|-------------|----------------|--|
| S8 | S8535 045923085352 | | 120-2 | 77 9 |) | 50/60Hz | | Z | 18, 26, G24d Socket; 13, 18, 26 G24q Socket | | PL | | G24d | | |
| Lamp Code | | | | | Dimmable/Non- Dimmable | | | n MOL In Inches | | Initial Lumens | Average Rated Hours | • | | Color | |
| 9WPLV/LED/827/BP/2P | | | | Non-Dimmable | | | Frost | 4-11/16" | | 900 | 50000 | 2700 | | Warm White | |
| CRI | CRI Beam Spread Deg Burning | | g Position | Pack | Pa | ackage Type | | CEC Status | | RoHS Complian | | t Warranty | | | |
| 82 | 12 | 20 | Vertical | Operation | 50/10 |) Box | | | Lawful for sale in California | | Yes | Yes | | 5 Year Limited | |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051