

S8536

9WPLV/LED/830/BP/2P 9W LED PL 2-Pin; 3000K; 950 Lumens; G24d base; 50000 Average rated hours; 120 Deg. beam spread; Vertical; Type B; Ballast Bypass

Features

- In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13, 18, and 26 watt CFLs

 • Ballast Bypass; Direct wire voltage range 100-277V
- Instant on to full brightness / no flickering
- Vertical operation
- Up to 70% energy saving



S8536

Installation Note: 2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.

Item Numb	er UPC	Voltage	Watts		erating quency	Fluoresce	nt Equivalent	Lamp Shape	Base
S8536	045923085369	120-277	9	50/60Hz		18, 26, G24d Socket; 13, 18, 26 G24q Socket		PL	G24d
Lamp Code		Dimmable/Non- Dimmable		Finish	MOL In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
9WPLV/LED/830/BP/2P		Non-Dimmable		Frost	4-11/16"	950	50000	3000	Soft White

CRI	Beam Spread Deg	Burning Position	Pack	Package Type	CEC Status	RoHS Compliant	Warranty
82	120	Vertical Operation	50/10	Box	Lawful for sale in California	Yes	5 Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051