

## S8538

9WPLV/LED/840/BP/2P 9W LED PL 2-Pin; 4000K; 1000 Lumens; G24d base; 50000 Average rated hours; 120 Deg. beam spread; Vertical; Type B; Ballast Bypass

## **Features**

- In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13, 18, and 26 watt CFLs

  • Ballast Bypass; Direct wire voltage range 100-277V
- Instant on to full brightness / no flickering
- Vertical operation
- Up to 70% energy saving

9WPLV/LED/840/BP/2P



S8538

50000

4000

White

Installation Note: 2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.

Non-Dimmable

Item Number	UPC	Voltage	Watts	Operating Frequency		Fluorescent Equivalent		Lamp Shape	Base
S8538	045923085383	120-277	9	50/	5U/6UH7		l Socket; 13, 18, 4q Socket	PL	G24d
Lamp Code		Dimmable/Non- Dimmable		Finish	MOL In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
0W/DLV/LED/840/RD/2D		Non-Dimmable		Froet	<b>1-11/16</b> "	1000	50000	4000	Cool

CRI	Beam Spread Deg	Burning Position	Pack	Package Type	CEC Status	RoHS Compliant	Warranty
82	120	Vertical Operation	50/10	Box	Lawful for sale in California	Yes	5 Year Limited

4-11/16"

1000

Frost



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051