

S8539

9WPLV/LED/850/BP/2P

9W LED PL 2-Pin; 5000K; 1000 Lumens; G24d base; 50000 Average rated hours; 120 Deg. beam spread; Vertical; Type B; Ballast Bypass

Features

- In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13, 18, and 26 watt CFLs Ballast Bypass; Direct wire voltage range 100-277V
- Instant on to full brightness / no flickering
- Vertical operation
- Up to 70% energy saving



S8539

Installation Note: 2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.

Item Number		ι	IPC	Voltaç	ge Wa	itts	ts Operating Frequency		Fluorescent Equivalent			.amp Shape	Base		
S85	S8539 045923085390		120-2	77 9)	50/60Hz		Z	18, 26, G24d Socket; 13, 18, 26 G24q Socket		8,	PL	G24d		
Lamp Code					Dimmable/Non- Dimmable				L In hes	Initial Lumens	Average Rated Hours	Kelv Ter	Color		
9WPLV/LED/850/BP/2P				Non-Di	Non-Dimmable			4-1 <i>°</i>	1/16''	1000	50000	50	00	Natural Light	
CRI	CRI Beam Spread Deg Burn		Burnin	g Position	Pack	Pa	ackage Type		С	EC Status	RoHS Com	RoHS Compliant		Warranty	
82	120 Vertical C		Operation	50/10	Box			Lawful for sale in California		Yes	Yes		5 Year Limited		



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051