

## S8610

4.5W EFC/LED/27K/120V 4.5 watt CA11 LED; Clear; Medium base; 2700K; 450 lumens; 120 volts; Carded

## Features

- LED with a traditional incandescent look and feel
  Omni-directional light source
  Smooth dimming
  Replaces up to 40 watt lamps
  Long life 15,000 hours
  Damp Location
  UL listed for totally enclosed fixtures



S8610

| Item Number UPC         |                           | Voltag                       | е         | Watts                     | Incandescent Equivalent Power Factor L |        |   | Lamp Shape              |       | Base        |                  |                            |                   |     |
|-------------------------|---------------------------|------------------------------|-----------|---------------------------|--|--------|---|-------------------------|-------|-------------|------------------|----------------------------|-------------------|-----|
| S8610 045923086106      |                           | 120                          |           | 4.5                       | 40W                                    |        | >0.70                                   |                         | CA11  |             | Medium           |                            |                   |     |
| ANSI<br>Base            |                           | Lamp Code                    |           | Dimmable/Non-<br>Dimmable |  | Sugges | sted Dimmers Fin                        |                         | ich - | L In<br>hes | MOD In<br>Inches |                            | Initial<br>Lumens |     |
| E26                     | E26 4.5W EFC/LED/27K/120V |                              | 20V       | Din                       | nmat                                   | ole    | Compat<br>dimmers fo                    |                         | Cle   | ear 4-5     | 5/16''           | 1.38"                      |                   | 450 |
| Average Rated Kelvin Co |                           | Col                          | lor (     | CRI                       | Beam Spread Op                         |        | Operati                                 | perating Temperature    |       | Pack        | Pac              | kage Type                  |                   |     |
| 15                      | 5000                      | 2700                         | Wai<br>Wh |                           | 80                                     | 36     | -20C (-4F) to a maximum of +45C (+113F) |                         | 12/1  | CD/1        |                  |                            |                   |     |
| ENER                    | GY STA                    | AR CEC Status RoHS Compliant |           |                           | UL or ETL<br>Listed UL Classification  |        | Warranty                                |                         |       |             |                  |                            |                   |     |
| ENER                    | GY STA                    | R Non-Com                    | oliant    | Yes                       |  | Υe     | es cUI                                  | cULus - Damp Location I |       |             | Rated            | ated <u>3 Year Limited</u> |                   |     |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051