

S8690

13T5/LED/46-835/BP/HE/120-277V 13W T5 LED; Miniature bi-pin base; 3500K; 50000 Average rated hours; 1600 Lumens; 120-277V; Type B; Ballast Bypass; Single Ended Wiring

Features

- No ballast or external driver required
- All glass tube
- PET–shatterproof coatedNSF Approved

S8690

Item Number		UPC	<u> </u>	Voltage '		/atts	atts Operating		equency	Lamp Shape	Base	ANSI Base	
S8690		045923086	908 1	120-277		13 5		50/60Hz		T5	Miniature Bi-Pin	G5	
Lamp Code			Finish	MOL Inch			D In ches	Initial Lumens		Average Rate Hours	ed Kelvin Temp	Color	
13T5/LED/46-835/BP/HE/1 277V			Frosted	48"		0.	0.88"		1600	50000	3500	Neutral White	
CRI	I Beam Operating Temperature Pa				Pack	CEC Status			С	DLC ID:	RoHS Compliant	UL or ETL Listed	
83	240	-20C (-4F) to a maximum of +45C (+113F)			25	Lawful for sale in California			PL8VVDCTNIUW DLC Search		Yes	Yes	
	UL Classification												
	cULus Classified - Damp Location Rated											5 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051