

## S8693

12T5/LED/24-835/BP/HO/120-277V 12W T5 LED; Miniature bi-pin base; 3500K; 50000 Average rated hours; 1400 Lumens; 120-277V; Type B; Ballast Bypass; Single Ended Wiring

## **Features**

- No ballast or external driver required
- All glass tube
- PETâ€"shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8693

Item	em Number UPC			Voltage		Watts	Operat	ing Frequency	Lamp Shape	Base	ANSI Base
S	S8693 045923086		939	120-277		12 5		50/60Hz	T5	Miniature Bi-Pin	G5
	Lamp Code			MOI Incl			DD In ches	Initial Lumens	Average Rat Hours	ed Kelvin Temp	Color
12T5/	12T5/LED/24-835/BP/HO/120- 277V			24	<b>!</b> ''		.88"	1400	50000	3500	Neutral White
CRI	RI Beam Spread Deg Operating Tempe		j Tempera	iture P	ack	CEC Status		RoHS Complia	UL or E <sup>-</sup> int Listed	i – III Class	ification
83	240	-20C (-4F) to a maximum of +45C (+113F)			25	Lawful for sale i California		in Yes	Yes	Yes cULus Classif Location	
Warranty											
5 Year Limited											



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

