

## S8694

12T5/LED/24-840/BP/HO/120-277V 12W T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 1450 Lumens; 120-277V; Type B; Ballast Bypass; Single Ended Wiring

## **Features**

- No ballast or external driver required
- All glass tube
- PETâ€"shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8694

Item	Number	mber UPC		Voltage	Wat	tts Opera	ating Frequency	Lamp Shape	Base		ANSI Base
S	S8694 045923086946		946	120-277	12	2	50/60Hz	T5	Miniature Bi-Pin		G5
	Lamp Code		Finisl	h MOI Incl	_ In nes	MOD In Inches	Initial Lumer	Average R ns Hours		Kelvin Temp	Color
12T5/	12T5/LED/24-840/BP/HO/120- 277V			ed 24	4''	0.88"	1450	50000	50000		Cool White
CRI	Beam Spread Deg	Pack	CEC Status		RoHS Compliant		UL or ETL Listed	UL Classification		า	Warranty
83	240	25	Lawful for sale in California		Yes		Yes	cULus Classified - Damp Location Rated		ear Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

