

## S8696

16T5/LED/36-835/BP/HO/120-277V 16W T5 LED; Miniature bi-pin base; 3500K; 50000 Average rated hours; 1800 Lumens; 120-277V; Type B; Ballast Bypass; Single Ended Wiring

## **Features**

- No ballast or external driver required
- All glass tube
- PETâ€"shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8696

Item	n Number UPC			Voltage	,	Watts	Operati	ng Frequency	Lamp Shape	Base	ANSI Base	
S	S8696 045923086		960	120-277		16 5		60/60Hz	T5	Miniature Bi-Pin	G5	
	Lamp Code			MOL Incl			DD In ches	Initial Lumens	Average Rat Hours	ted Kelvin Temp	Color	
16T5/LED/36-835/BP/HO/120- 277V			Frosted	36	)''	C	.88"	1800	50000	3500	Neutral White	
CRI	Beam Spread Deg	Operating Lemperature		ture P	ack	CEC Status		RoHS Complia	UL or E	·	ification	
83	240	-20C (-4F) to a maximum of +45C (+113F)			25	Lawful for sale in California		in Yes	Yes		cULus Classified - Damp Location Rated	
Warranty												
<u>5 Year Limited</u>												



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

