

S8706

25WLED/CDL/6/4K/100-277 25 watt Commercial LED Downlight Retrofit; 6 inch; 4000K; 100-277 volts

Features

- Solid State LED lighting
- External driver for simple retrofitting
- Quick connect feature for easy installation
- 100-277 range voltage circuit
- 0-10V dimming



80-937 6" mounting plate for commercial recessed downlights.



S8706

UPC	Voltage Watts		Fixture Type	Base	La	amp Code	Dimmable/Non- Dimmable		
5923087066	100-277	25	Retrofit Connecto		25WLED/	CDL/6/4K/100	0-10V Dimming Only		
MOL In Inches MOD In Inches Initial Lumens		Average Rated Hours		Kelvin Temp	Color	CRI	RoHS Compliant		
7-1/2"	1900		50000		4000	Cool White	90	Yes	
UL Classification						Warranty 5 Year Limited			
	5923087066 MOD In Inches 7-1/2"	5923087066 100-277 MOD In Inches Initial Lu 7-1/2" 190 UL Class	5923087066 100-277 25 MOD In Inches Initial Lumens 7-1/2" 1900 UL Classification	OPC Voltage Watts Type 5923087066 100-277 25 Retrofit MOD In Inches Initial Lumens Average Hou 7-1/2" 1900 500	Type Base Type Base 5923087066 100-277 25 Retrofit Connector MOD In Inches Initial Lumens 7-1/2" 1900 50000 UL Classification	Type Base Li 5923087066 100-277 25 Retrofit Connector 25WLED/ MOD In Inches Initial Lumens Average Rated Hours Kelvin Temp 7-1/2" 1900 50000 4000 UL Classification	Type Base Lamp Code Type Base Lamp Code	Type Base Lamp Code Type Base	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

